



ТЕХНОЛОГИИ СОЗДАНИЯ САЙТОВ

HTML

(ЯЗЫК РАЗМЕТКИ ГИПЕРТЕКСТА)

- Любой текстовый редактор (Блокнот; Word; OpenOffice.org)
- Специальное программное обеспечение (Adobe Dreamweaver; Nvu)
- Конструктор сайтов (uCOZ; Jimbo; Сайткрафт)

```
<html>
<head>
<title>HTML CONSTRUCTION: советы по созданию, размещению и индексированию HTML-сайтов</title>
<meta http-equiv="Content-Type" content="text/html; charset=windows-1251">
<meta name="description" content="личный сайт организатора группы Strangers">
<meta name="keywords" content="Ох, дети Индиго, Indigo, Strangers, Путники, рок, рок, группа">
<meta name="author" content="Smoren">
<link rel="stylesheet" href="1.css" type="text/css" media="all"/>
</head>
<!--Copyright (c) by smoren 2006.-->
<body background="images/01.jpg" marginwidth="0" marginheight="0" leftmargin="0" rightmargin="0"
style="scrollbar-3d-light-color: #B98B9C;
scrollbar-arrow-color: #7A8DFF;
scrollbar-face-color: black;
scrollbar-track-color: #7A8DFF;
scrollbar-dark-shadow-color: black;
scrollbar-highlight-color: #BAE1FE;
scrollbar-shadow-color: black">
<table border=0 cellspacing=0 cellpadding=0 bgcolor=black width=100%><tr>
<td width=100></td>
<td width=* align=center></p></a></td></tr></table>
<table border=0 cellspacing=0 cellpadding=0 height=5><tr><td></td></tr></table>
<table border=1 bordercolor=#BAE1FE cellspacing=0 cellpadding=0 width=100%><tr>
<td align=center width=70 class=normal1 onMouseOver=
    "this.className='selected1'"
    onClick="javascript:location.href=
    'index.html'"
    onMouseOut="this.className='normal1'">
    <font face=verdana size=2>Главная</font></td>
<td align=center width=110 class=normal1 onMouseOver=
    "this.className='selected1'"
    onClick="javascript:location.href=
    'first.html'">
```

```

73 <nav data-iconpos="top" data-role="navbar" >
74   <ul>
75     <li><a id="locBtn" href="#locator" data-theme="h">Locator</a></li>
76     <li><a id="styleBtn" data-theme="h">StyleMaker</a></li>
77     <li><a id="popBtn" href="#popup" data-theme="h">Popup Sto</a></li>
78     <li><a id="chartBtn" data-theme="h">Size Chart</a></li>
79     <li><a id="salesBtn" href="#home" data-theme="h">Sales</a></li>
80   </ul>
81 </nav>
82 </div>
83 </div>
84 <div data-role="page" id="store" data-add-back-btn="true" >
85   <div data-role="header" data-theme="g" >
86     <h1>Store Location</h1>
87     <!--<a class="ui-btn-right" href="#storeMap" data-role="butto
88     <div data-role="content" data-theme="h" >  <a href="tel:877-987-6543" id="contactsBtn" data-
data-inline="true" data-role="button" data-theme="h" >Call</a>
89     <p><span class="street">2349 Glendale Blvd.</span><br>
90     <span class="city">Los Angeles, CA</span><br>
91     877-987-6543</p>
92     <p><span class="hilit">Store Hours:</span><br>
93     10am to 9pm, Mon - Sat; <br />11am to 7pm, Sun
94 </p>
95 <section>
96   <h3>In-Store This Week</h3>
97   <p>Secret sale on shoes and accessories. Up to 40% off selec
98 </section></div>
99
100 <div data-role="footer" data-position="fixed" data-id="persistantFooter">
101 <nav data-role="navbar" data-iconpos="top">
102   <ul>
103     <li><a id="locBtn" href="#locator" data-theme="h">Locator</a></li>
104     <li><a id="styleBtn" data-theme="h">StyleMaker</a></li>
105     <li><a id="popBtn" href="#popup" data-theme="h">Popup Store</a></li>
106     <li><a id="chartBtn" data-theme="h">Size Chart</a></li>
107     <li><a id="salesBtn" href="#home" data-theme="h">Sales</a></li>
108   </ul>

```

jQuery Mobile Swatches

BUTTON THEME

Theme: 'h'

BUTTON ICON

Icon: 'grid'

BUTTON ICON POSITION

Default Left Right

[Get More Themes](#)

STORE LOCATION



2349 Glendale Blvd.
Los Angeles, CA
877-987-6543

STORE HOURS:
10am to 9pm, Mon - Sat;
11am to 7pm, Sun

IN-STORE THIS WEEK

Secret sale on shoes and accessories. Up to 40% off select items!

Locator StyleMaker Popup Store Size Chart Sales

Adobe BrowserLab

Insert CSS Transitions

CSS Styles AP Elements

All Current

Summary for Selection

cursor	pointer
text-decoration	none
white-space	nowrap
position	relative
z-index	1

Rules

Properties for ".ui-btn-text"

Business Catalyst

Files Assets

Local Files

Local Files	Size	Type
Site - Pluralis...		Folde
assets		Folde
index.html	8KB	HTML
jquery-m...		Folde

1 local items selected tot [Log...]

<body...> <div...> <div...> <a...> <span.ui-btn-inner.ui-btn-corner-all> <span.ui-btn-text>

100% 382 x 619 764K / 16 sec Unicode (UTF-8)

Properties

HTML Format None Class None Title

CSS ID contactsBtn Link tel:877-987-6543 Target

Page Properties... List Item...

Управление сайтами

Список сайтов Создание сайта Настройки

Сайт создан

Сайт "test-video.ucoz.ru" успешно создан.

В панели управления сайтом используется Веброн пароль.

Вы можете изменить этот пароль в панели управления сайтом, раздел "Безопасность".

Панель управления сайтом

После создания к сайту можно прикрепить любой персональный домен, например, "mysite.com".

PHP

«ПРЕДВАРИТЕЛЬНЫЙ ОБРАБОТЧИК ГИПЕРТЕКСТА»

- PhpStorm
- Sublime Text
- PHP Studio

Project Structure

- testproject (/Applications/MAMP/hdocs)
 - demo
 - cache
 - configs
 - plugins
 - templates
 - templates_c
 - index.php
 - docs
 - img
 - js
 - less
 - libs
 - .gitignore
 - .travis.yml
 - component.json
 - composer.json
 - CONTRIBUTING.md
 - LICENSE
 - localhost.sql
 - Makefile
 - mysql-connector-java-5.1.18-bin.jar

```

resource.extendsall.php
extend.html
test.html
index.php

$smarty = new Smarty;

$smarty->debugging = false;
$smarty->cache_ = true;
$smarty->cache_id = null|string;
$smarty->cache_lifetime = int;
$smarty->cache_locking = bool;
$smarty->cache_modified_check = bool;
$smarty->_cache_resource_handlers = array;
$smarty->registered_cache_resources = array;

$smarty->assign("contacts", array(array("phone" => "555-4444", "fax" => "555-4444"), array("phone" => "555-4444", "fax" => "555-4444")));

$smarty->assign("option_values", array("NY", "NE", "KS", "IA", "OK", "TX"));
$smarty->assign("option_output", array("New York", "Nebraska", "Kansas", "Iowa", "Oklahoma"));
$smarty->assign("option_selected", "NE");

$smarty->display('index.tpl');

```

Documentation for cache_id

\$cache_id = null|string

Set this if you want different sets of cache files for the same templates.

Declared In: [Smarty](#)

Database

- columns_priv: table
- db: table
 - Host: varchar(60)
 - Db: varchar(64)
 - User: varchar(16)
 - Select_priv: enum('N', 'Y')
 - Insert_priv: enum('N', 'Y')
 - Update_priv: enum('N', 'Y')
 - Delete_priv: enum('N', 'Y')
 - Create_priv: enum('N', 'Y')
 - Drop_priv: enum('N', 'Y')
 - Grant_priv: enum('N', 'Y')
 - References_priv: enum('N', 'Y')
 - Index_priv: enum('N', 'Y')
 - Alter_priv: enum('N', 'Y')
 - Create_tmp_table_priv: enum('N', 'Y')
 - Lock_tables_priv: enum('N', 'Y')
 - Create_view_priv: enum('N', 'Y')
 - Show_view_priv: enum('N', 'Y')
 - Create_routine_priv: enum('N', 'Y')
 - Alter_routine_priv: enum('N', 'Y')
 - Execute_priv: enum('N', 'Y')
 - Event_priv: enum('N', 'Y')
 - Trigger_priv: enum('N', 'Y')
 - User: (User)
- event: table

Debug Console

Debugger

Frames

- Index.php:22, {main}()

Variables

- \$smarty = {Smarty} [82]
- \$_COOKIE = {array} [3]
- \$_ENV = {array} [15]
- \$_REQUEST = {array} [3]
- \$_SERVER = {array} [30]

interactive.py

```

1  -*- coding: utf-8 -*-
2  #
3  # Copyright (C) 2006-2007 Alec Thomas <alec@swsopoff.org>
4  #
5  # This software is licensed as described in the file COPYING, which
6  # you should have received as part of this distribution.
7  #
8
9  """CLY and readline, together at last.
10
11 This module uses readline's line editing and tab completion along w
12 grammar parser to provide an interactive command line environment.
13
14 It includes support for application specific history files, dynamic
15 customisable completion key, interactive help and more.
16
17 Press ``?`` at any location to contextual help.
18 """
19
20 import os
21 import sys
22 import readline
23 import cly.rlexit
24 import cly.console as console
25 from cly.exceptions import Error, ParseError
26 from cly.builder import Grammar
27 from cly.parser import Parser
28
29
30 __all__ = ['Interact', 'interact']
31 __docformat__ = 'restructuredtext en'
32
33
34 class Interact(object):
35     """CLY interaction through readline. Due to readline limitation:
36     Interact object can be active within an application.
37
38     Constructor arguments:
39
40     ``parser``: ``Parser`` or ``Grammar`` object
41         The parser/grammar to use for interaction.
42
43     ``application='cly'``: string
44         The application name. Used to construct the history file name
45         prompt, if not provided.
46
47     ``prompt=None``: string
48         The prompt.

```

interactive.py

```

71     ``help_key='?'``: `key`
72         Key to use for tab completion.
73
74     """
75     _cli_inject_text = ''
76     _completion_candidates = []
77     _parser = None
78     prompt = None
79     user_context = None
80     history_file = None
81     application = None
82
83     def __init__(self, grammar_or_parser, application='cly', prompt=
84                 user_context=None, with_context=None, history_file=
85                 history_length=500, completion_key='tab',
86                 completion_delimiters=' \t',
87                 help_key='?', inhibit_exceptions=False,
88                 with_backtrace=False):
89
90         if prompt is None:
91             prompt = application + '> '
92         if history_file is None:
93             history_file = os.path.expanduser('~/.%s_history' % app)
94         if isinstance(grammar_or_parser, Grammar):
95             parser = Parser(grammar_or_parser)
96         else:
97             parser = grammar_or_parser
98
99         if with_context is not None:
100             parser.with_context = with_context
101         if user_context is not None:
102             parser.user_context = user_context
103         Interact._parser = parser
104         Interact.prompt = prompt
105         Interact.application = application
106         Interact.user_context = user_context
107         Interact.history_file = history_file
108         Interact.history_length = history_length
109         Interact.completion_delimiters = completion_delimiters
110         Interact.completion_key = completion_key
111
112     try:
113         readline.set_history_length(history_length)
114         readline.read_history_file(history_file)
115     except:
116         pass
117
118     readline.parse_and_bind("%s: complete" % completion_key)
119     readline.set_completer_delims(self.completion_delimiters)

```


PHP Studio 2009 - [Untitled0.php*]

File Edit Search View Insert Project Run Tools Window Help

PEAR.php hello.php phpinfo.php Untitled0.php*

File Explorer

- www.cayoren.com
 - .svn
 - download
 - inside
 - issues
 - media

Name

- features.php
- index.php
- media.php
- php-studio.xml
- screenshot.php
- shared.php

All Supported Formats

Project ... File Expl...

Output

No syntax errors detected in C:\Program Files\PHP Studio 2009\project\Untitled0~tps~.php

Environment Options

Environment Options

PHP Internal HTTP Server External HTTP Server

PHP Interpreter C:\Program Files\PHP\php-cgi.exe

PHP.INI File C:\Program Files\PHP\php.ini

PHP Help File C:\Program Files\PHP\php_manual_en.chr

PHP Extension(s) *.php;*.php3;*.phtml;*.inc

Apply Cancel

Code Library

PHP 5 Functions

- Apache-specific Functions
- Array Functions
- Aspell functions [deprec]
- BCMath Arbitrary Preci
- Bzip2 Compression Fun
- Calendar functions
- CCVS API Functions
- Class/Object Functions
- COM support functions t
- ClibPDF functions
- Crack functions
- Character type function
- CURL, Client URL Librar
- Cybercash payment fur
- Crdit Mutuel CyberMUT

Code Ex... Code Li...

Output Search Results Server Logs

11: 3 Insert Modified PHP+HTML+XML+CSS+JS Select the location of PHP configuration file

Brothersoft

The image features a dark blue gradient background. In the corners, there are decorative white line-art patterns resembling circuit board traces and nodes. The word "КОНЕЦ" is centered in the upper left quadrant.

КОНЕЦ