

RISK ASSESSMENT – A ROPE ACCESS PERSPECTIVE

ALAN FORREST

- IRATA Lead Auditor
- IRATA Assessor & Instructor
- Original IRATA Level 3 – North Sea 1989
- Worldwide Independent Consultant



MOSCOW 2016

WHAT IS A RISK ASSESSMENT?

Some Definitions:

- A systematic process of evaluating the potential risks that may be involved in a projected activity or undertaking.
- Specific and detailed work instruction for the effective protection of all members of the work team and others affected by their actions.
- A risk assessment is not about creating huge amounts of paperwork, but rather about identifying sensible measures to control the risks in your workplace.



MOSCOW 2016

TERMINOLOGY

- **Hazard** – Potential danger.
- **Risk** - Likelihood of hazard resulting in a negative outcome.
- **Consequence** – Negative outcome.
- **Control** - Eliminating, or minimising, the potential for a negative outcome.



MOSCOW 2016

UK LEGAL PERSPECTIVE

Management of Health & Safety at Work Regulations 1999:

3,- (1) Every employer shall make a suitable and sufficient assessment of –

(a) the risks to the health and safety of his employees to which they are exposed whilst they are at work; and

(b) the risks to the health and safety of persons not in his employment arising out of or in connection with the conduct by him of his undertaking.



MOSCOW 2016

WHO IS THE RISK ASSESSMENT FOR?

- The company?
- The client?
- The workers?
- The auditor?
- The judge?



MOSCOW 2016

WHO IS PREPARING THE RISK ASSESSMENT?

- The company or supervisor?
- Blank page or generic?
- Training and assessment
- Qualification and capability.



MOSCOW 2016

WHO IS CHECKING AND ACCEPTING THE RISK ASSESSMENT?

- Client representatives.
- Are they familiar enough with specialist activities to make informed judgments?
- Educate clients to help their understanding – training, demonstration, explanation ...
- A client who understands what he is looking at is liable to be more relaxed and understanding towards “unusual” activity in their facility.



MOSCOW 2016

INITIAL COMMUNICATION & UNDERSTANDING

- **Supervisors** – Involved in preparation, experienced and alert to environment.
- **Workers** – Initial communication and understanding, layout and presentation, language.
- **Declaration with Signatures:**
“I have been fully briefed in the attached risk assessment, I understand all aspects of it and agree to follow its contents. Particularly, I understand my personal roles and responsibilities with the team”



MOSCOW 2016

ONGOING COMMUNICATION & UNDERSTANDING

Meaningful pre-work meetings:

- Daily Work Plan
- Risk Assessment Daily Review
- Access Method
- Rigging Considerations
- Hazards to rope
- Rescue Plan
- Individual Team Member Roles
- Exclusion Zones
- Tools & Materials
- Weather



MOSCOW 2016

WHO IS ULTIMATELY RESPONSIBLE?

The Company, was fined £100,000 after pleading guilty to breaching Regulation 4 of the Work at Height Regulations 2005.

Following the case, the HSE Inspector, said:

“This was a tragic incident and the death could have been prevented had The Company planned the job correctly and put suitable safety measures in place.

“Assessing the risks of that job properly would have identified that the potentially sharp edge presented a very clear danger to anyone suspended and working on ropes rigged against it.

“However, the company failed to do this so failed to take safety precautions and instead, The Individual fell to his death.”



MOSCOW 2016

RISK ASSESSMENT IS A PROCESS

The UK Health and Safety Executive's Five Steps to Risk Assessment.

- Step 1: Identify the hazards.
- Step 2: Decide who, or what, might be harmed and how.
- Step 3: Evaluate the risks and decide on precautions.
- Step 4: Record your findings and implement them.
- Step 5: Review your risk assessment and update if necessary.



MOSCOW 2016

STEP 1: IDENTIFY THE HAZARDS

FALLING	DROPPED OBJECTS	RESCUE	TOOLS & MATERIALS	WORKSITE	WORKSITE	ENVIRONMENTAL
Anchor Failure	Technician struck on rope	Lack of competence of personnel	Causing injury	Conflicting activities	Gas	Wind
Technician losing control	Others struck by rope access team	Lack of planning & preparation	Causing ill-health	Communications	Electricity	Rain / Snow
Lack of training & competence		2-person loads	Damaging access equipment	Chemicals	Radiation / Radio waves	Heat
Cut rope: sharp, hot surfaces, etc		Level 3 on ropes	Contaminating rope	Dust	Slips & Trips	Cold
Equipment Failure		Time / suspension trauma		Noise	Fragile surfaces	Lightning
Unattached at exposed edges				Hot surfaces	Confined spaces	Darkness / Visibility
Working in fall arrest				Vibration	Great heights	Waves / Current
Lead climbing				Asbestos	Direct attacks from public	
Abseiling off end of rope				Vermin		

STEP 2: DECIDE WHO, OR WHAT, MIGHT BE HARMED AND HOW

WHO?

- Our work team, including varying capabilities and experience within the team.
- Other workers on site.

WHAT?

- Property and equipment damage.
- Environmental damage.



MOSCOW 2016

STEP 3: EVALUATE THE RISKS.

LIKELIHOOD	Regular Occurrence	5	5 GREEN	10 AMBER	15 RED	20 RED	25 RED
	Fairly Frequent	4	4 GREEN	8 AMBER	12 RED	16 RED	20 RED
	Occasional Occurrence	3	3 GREEN	6 AMBER	9 AMBER	12 RED	15 RED
	Remotely Possible but Known	2	2 GREEN	4 GREEN	6 AMBER	8 AMBER	10 AMBER
	Highly Improbable	1	1 GREEN	2 GREEN	3 GREEN	4 GREEN	5 GREEN
			1	2	3	4	5
			Minor Injuries	Lost Time Injuries	Major Injuries	Permanent Disabilities	Fatality
			SEVERITY				



MOSCOW 2016

STEP 3: DECIDE ON PRECAUTIONS (CONTROLS).

There is a hierarchy of approach when considering control measures:

- Remove the hazard completely
- Try a less hazardous material or option
- Prevent access to the hazard
- Organise work to reduce exposure to the hazard
- Increase level of information, training and supervision
- Issue PPE and provide welfare facilities



MOSCOW 2016

STEP 4: RECORD YOUR FINDINGS

Format 1 – using matrix

Job Steps	Hazard		Initial Risk (from matrix)			Controls	Residual Risk (from matrix)		
	Hazard description and effect	People, Property or Environment at Risk	Hazard Consequence	Chance of Occurrence	Risk Rating		List All Controls Required	Controlled Hazard Consequence	Controlled Chance of Occurrence

- Repetitive
- Complex
- Subjective
- Attempt to be quantitative



MOSCOW 2016

STEP 4: RECORD YOUR FINDINGS

Format 2 – No Matrix

What are the hazards?	Who might be harmed and how?	What are you already doing?	What further action is necessary?	Residual Risk (from matrix)	Action by whom?	Action by when?	Date carried out

- Less complex
- Less subjective
- More qualitative than quantitative



MOSCOW 2016

STEP 5: REVIEW THE RISK ASSESSMENT.

Things change - review what you are doing on an ongoing basis:

- Have there been any significant changes in your environment?
- Can you make any improvements?
- Has anyone noticed a problem?
- Have you learnt anything from accidents or near misses?
- Make sure your risk assessment stays up to date.



MOSCOW 2016

Hazard Identify the danger	Consequence Who / what will be affected?	Control Eliminate or minimise risk
ANCHOR FAILURE	Free-fall leading to severe injury or death of technician	<ul style="list-style-type: none"> • Anchor points must be assessed as “unquestionably reliable” by a competent person. • Minimum strength requirement for rope access anchors is 15kN. • Minimum strength requirement for fall arrest anchors is 12kN. • All anchor systems must consist of two fully independent systems – one for the working rope and one for the back-up rope. • Both anchor points can be attached to one substantial structural or natural feature. • Rigging should account for the failure of one anchor point and the consequences of that failure must be kept to a minimum. • Load sharing between anchor points is desirable where possible. • Angles within anchor systems must be kept to a minimum: 90° preferred maximum, 120° absolute maximum – critical angle. • Direction of loading must be considered, particularly for Tripods, “A” Frames, etc. • Training and competence in installation and testing of specialist, or unfamiliar, anchor systems is essential. • Bolts in masonry, concrete, brickwork, block-work and rock must be competently installed by a competent person and tested prior to use. • Bolts in such material must be rigged in pairs in a load sharing system. • If any doubt exists an engineer must be consulted. • Other ...

Hazard Identify the danger	Consequence Who / what will be affected?	Control Eliminate or minimise risk
<p>CUT ROPE</p> <p>Sharp, abrasive, hot surfaces</p> <p>chemical contamination</p> <p>hot work</p> <p>cutting tools</p> <p>adjacent operations</p>	<p>Free-fall leading to severe injury or death of technician</p>	<ul style="list-style-type: none"> • It is essential that the intended path of the ropes is checked thoroughly prior to operations commencing. Where a hazard is identified it should be dealt with in the following order of preference: • Remove, or neutralise, the hazard where possible. This can be done by removing or isolating the source of the hazard or neutralising the hazard, e.g. by building a protective cover over it. • Avoid the hazard by rigging. First try to get anchor points that allow you to directly vertically access the worksite from above, whilst at the same time avoiding the hazard. Where this is not possible try to rig away from the hazard using rigging techniques such as: Y-hangs, protection (double) deviations, or rebelay. • Protect against the hazard by utilising suitable and sufficient protection equipment, including: edge rollers, edge protectors and rope protectors appropriate to the level of risk presented by the hazard. • Wire sling bypass arrangements may also be considered as a further layer of protection. • When using rope protectors over an edge, each rope should have its own rope protector. In addition the edge should also be protected. • Particular care should be taken when passing rope protection to ensure that levels of protection are not compromised when opening and closing protection. • In order to offer sufficient protection the surface or edge should be increased to greater than 5mm and covered with a layer of suitable and sufficient padding. • Rope protectors should be attached to the ropes with a solid link, e.g. an Alpine Butterfly knot, or a rope grab (prussik knots, although commonly used to attach rope protectors are subject to interference and a non-expert technician is at risk of not re-installing the protection properly resulting in the protector loosening and falling down the rope, thus rendering it useless). • Combinations of these measures should be considered where possible. • When working with cutting or burning tools measures must be taken to protect the ropes and other equipment directly around the technician. Measures may include a wire lanyard attached to a back-up device placed well above the technician, protective aprons, or use of a mobile work platform. Excess rope should be bagged out of harms way. • Some of these protection methods can present a significant obstacle to inexperienced technicians. The supervisor should account for this when selecting the method of protection and the personnel to access the job. • Other ...

Hazard Identify the danger	Consequence Who / what will be affected?	Control Eliminate or minimise risk
NEW AND INEXPERIENCED TECHNICIANS	Errors leading to severe injury or death of technician	<ul style="list-style-type: none"> • New and inexperienced technicians must be constantly supervised and given simple access tasks at first. • Technicians must be trained and competent in the equipment that they have been issued with. • Supervisor and “buddy” checking must take place as a technician gets on a set of ropes at the top. Particular attention must be paid to the correct installation of descender and back-up device. • Descenders with an anti-panic feature are desirable for inexperienced technicians. • Back-up devices that require minimum manual adjustment and that cannot be defeated by the technician are desirable for inexperienced technicians. • A short function check should be performed before the main descent begins, ideally this will take place in a safe position before fully suspended. • Descent must be careful, slow and controlled. • Descender to be locked and back-up to be pushed high on arrival at the workface. • Extra care, including extra friction, should be used on wet or slippery ropes. • Supervisor may consider use of mid-rope stopper knots. • In extreme cases supervisor may consider the use of an independently controlled back-up rope. • Other ...

Hazard Identify the danger	Consequence Who / what will be affected?	Control Eliminate or minimise risk
<p>ABSEILING OFF END OF ROPE</p> <p>STRIKING OBSTACLES OR GROUND DUE TO INATTENTION</p>	<p>Errors leading to severe injury or death of technician</p>	<ul style="list-style-type: none"> • Suitable Stopper Knots must be tied at least 1m from the ends of each rope when working with short ropes on high structures. • Bagged ropes must be checked to ensure that they have suitable stopper knots and that the bag is attached to the rope ends. Technicians should bag their own ropes. • Suitable, mid-rope “reminder stopper knots”, e.g. Alpine Butterflies, can be tied a safe distance from the ground when ropes touch the ground, or above dangerous obstacles on the workface, where the line of the ropes passes an obstacle or protrusion. As the technician arrives at the knot, the knot can be untied and safe descent continued to the ground or around the obstacle. • Technicians must always be alert and aware of their surroundings – reaching the end of the rope, or the ground, should not be a surprise! • Other ...

Hazard Identify the danger	Consequence Who / what will be affected?	Control Eliminate or minimise risk
WIND CONDITIONS	Potential for injury to technician due to lack of control, or entanglement	<ul style="list-style-type: none"> • Get an accurate measure of wind speed for the area that you will be working in. • Work within agreed wind limits*. • Continue to monitor wind speeds during the course of your work. • Be aware that certain buildings and structures can create unusual and turbulent wind conditions. • Control rope ends to avoid them becoming entangled. • Ensure that your communication method is effective in windy conditions. • Consider whether the technicians have the experience to work safely in windy conditions. • If you are working in dusty conditions wear suitable eye protection. • If possible change the daily work plan to work in an area out of the wind. • If work cannot be conducted safely stop work until the wind speed has decreased. • Other ...

Hazard Identify the danger	Consequence Who / what will be affected?	Control Eliminate or minimise risk
HEAT & SUN	Potential for heat stroke, heat exhaustion and sunburn to technicians	<ul style="list-style-type: none"> • Get an accurate measure of temperature for the area that you will be working in. • Work within agreed maximum heat limits*. • Wear appropriately light clothing. • Ensure adequate hydration is available at all times. • Take regular rest breaks out of the sun. • Technicians should monitor each other for signs of heat exhaustion and sunstroke. • Protect exposed skin with suitable sun block and clothing. • If possible change the daily work plan to work at cooler times of day. • Allow for acclimatisation, e.g. a European technician arriving in Dubai for the first time. • If work cannot be conducted safely stop work until temperature is within acceptable limits. • Other ...

OBJECTIVES

- Engage all technicians in process.
- Enable Supervisors through training.
- Involve clients in the process by educating them so that they know what is going on.
- Maintain and enhance the safety record and reputation of rope access in industry worldwide.



MOSCOW 2016



Questions?

Comments?

alan@ffzero.com

AWS

MOSCOW 2016